

Double acting, Plain ram hydraulic jack



Features:

- Base mounting and collar threads are optional.
- HardChrome plating to avoid corrosion score mark.
- Used in vertical and horizontal directions.
- Maintenance, Pile Testing, Ship Ind., Box Pushing and etc.
- Maximum working pressure @700 BAR.

Model	Capacity	Stroke	Close Height	Cylinder OD (D)	Cylinder ID (d)	Ram OD	Weight (Approx)
	ton	mm	mm	mm	mm	mm	kg
MDP	10	150	275	75	45	30	8
MDP	15	150	280	85	55	40	11
MDP	20	150	285	95	63	50	14
MDP	25	150	295	95	70	55	14.3
MDP	30	150	305	100	75	55	15.6
MDP	50	150	305	130	100	70	26.3
MDP	75	150	305	160	120	90	38.5
MDP	100	150	310	180	140	110	53.5
MDP	150	150	320	220	170	140	84
MDP	200	150	345	255	200	150	116
MDP	250	150	350	280	220	180	148
MDP	300	150	365	310	240	180	181
MDP	400	150	385	350	270	220	255
MDP	500	150	450	400	300	250	425
MDP	600	150	475	440	330	280	490
MDP	800	150	500	510	360	300	700

Note:-

- Higher capacity customized solutions on request.
- Plating or painting on demand.